

BUTYLCELLOSOLVE (Industrial Grade)

TU 6-01-646-84

Butylcellosolve is used as solvent or component of solvents by production of polyether (alkyd) resins, enamels, varnishes, paints; as hydraulic fluids, retarding agent against dimness of varnish surface, as component for metal electro-polishing mixtures.

MAIN QUALITY SPECIFICATIONS

| | PREMIUM GRADE | 1 ST GRADE |
|---|---------------|-----------------------|
| Butylcellosolve Mass Content, %, min. | 99.0 | 96.5 |
| Density at 20°C, g/cm³ | 0.898 – 0.904 | 0.898 – 0.904 |
| Platinum Cobalt Scale Colour, Hazen, max. | 10 | 30 |
| Water Mass Content, %, max. | 0.20 | 0.25 |
| Saponification Number, mg KOH/g of product, max. | 1.0 | 1.5 |
| Refractive Index at within batch | 1.416 – 1.422 | - |

- Supply Form:** Colorless transparent liquid with slight odor
- Packaging:** Product is shipped in railway tank-cars
- Transportation:** Product may be transported in railway tank-cars by all covered transportation means in accordance with the current Rules for Transportation of Dangerous Goods.
- Storage:** Product shall be stored away from open fire in containers on open area, which shall meet the requirements of storage facilities for flammable and poisonous substances. Expire date is 3 months from the production date.

NIZH YUG - MAIN COMMERCIAL & MARKETING OFFICE

Ruzgarlibahce Sokak, Yasa IS Merkezi, Blok 1, Kat: 5-6 Kavacik/Beykoz, Istanbul – TURKIYE
Tel: +90 215 538 09 00 Fax: + 90 216 425 18 04 <http://www.nizhyug.com>



OJS 'KAZANORGSINTEZ'